



+ More



Versatile, ErgonomicAND EFFICIENT

Miller Weldmaster T300 Extreme® combines versatility and precisely controlled operating parameters within an ergonomic design and interface for easy operation, speed, accuracy, and productivity.

Hot Air & Wedge Welding Applications:

- •Woven Polypropylene
- •Woven Polyethylene
- •PVC Laminate
- •PVC Coated
- •Polyurethane Coated
- Polypropylene
- Acrylic
- +More...



Seam Types



















MILLER FILL

Technical Specification

Power Requirements: 208-240 Volts - Single Phase - 25 Amp. 380-400 Volts - Single Phase - 16 Amp.

Air Requirements: 2cfm @ 100psi

Power Consumption: Approx. 6kW

Maximum Temperature: Hot Air: 730°C/1,346°F

Hot Wedge: 450°C/842°F

Throat Width: 1m (39")

Dimensions: Width: 0.6m (23")

> Length: 1.5m (59") Height: 1.5m (59")

Weight: 231kg/510lb

Seam Width: 10-50mm (0.5-2")**

Welding Cycle: Up to 30m/min (100ft/min)*

FEATURES & BENEFITS

- 1. Easy operation touch screen and 25 memory settings.
- 2. Easy to use for any operator.
- 3. Quick, repeatable, precision head adjustments.
- 4. Available in hot air, hot wedge or equipped with both for product versatility.
- 5. Quick, easy guide change for multiple seam configurations.